What is claimed is:

1. A reclining massager system, comprising:

a) a base;

b) a back support to place a user's back and neck thereon when the user is seated in the base, wherein the back support has a cover, first and second ends, wherein the first end is rotatably connected to the base in a controllably reclining format;

c) a rider making a lengthwise reciprocal movement between the first and second ends of the back support;

d) a lifter liftedly engaged to the rider so that the lifter makes a forward reciprocal movement perpendicular to the lengthwise reciprocal movement of the rider; and

e) massage bumps veiled by the cover and attached atop the lifter to massage along the user's back and neck in accordance with the relative movements of the rider and lifter.

2. The reclining massager system of claim 1 wherein the lifter comprises:

a) a roller gear engaged to and powered by a first motor, wherein the first motor is fixed to the rider;

b) a bump support having a top portion and a bottom portion, wherein the massage bumps are mounted on the top portion; and

c) an engagement body downwardly extending from a bottom portion of the bump support, wherein a lower portion of the engagement body is releasably inserted in and fittingly supported by the rider, wherein an opening is formed through the engagement body to define inner walls, wherein one of the inner walls is configured to a rack gear so that the first roller gear is rollably engaged to the rack gear, whereby the roller gear rotation by the first motor enables the lifter to make the forward reciprocal movement.

3. The reclining massager system of claim 1 wherein the lifter comprises:

a) a bump support having a top portion and a bottom portion, wherein the massage bumps are mounted on the top portion; and

b) a gear unit including a bolt gear downwardly extending from the bottom portion of the bump support, an elongated nut type gear having a circular outer periphery, a first gear incorporated on and along the circular outer periphery, and a second gear engaged to the first gear and connected to a first motor attached to the rider, wherein the bolt gear is releasably engaged in the nut type gear whose bottom end is rotatably attached to and supported by the rider, whereby the second gear rotation generates the first gear rotation and the subsequent rotation of the nut type gear enables the lifter to make the forward reciprocal movement in accordance with the releasable engagement of the bolt gear and the nut type gear.

4. The reclining massager system of claim 1 wherein the massage bumps are partitioned to first and second pairs, wherein said each pair bumps are aligned parallel to the direction of the rider reciprocation.

5. The reclining massager system of claim 1 further comprising:

a) first and second bump holders propping and maintaining the first and second pair bumps, wherein the first and second bump holders are tapered toward each lower end thereof;

b) a first engagement member to rockingly engage the lower ends of the bump holders to the top portion of the lifter; and

c) a second engagement member to rollingly engage the massage bumps thereto.

6. The reclining massager system of claim 1 wherein the massage bumps each include a heater.

7. The reclining massager system of claim 6 wherein the heater is a heating lamp generating heat and infrared rays.

8. The reclining massager system of claim 1 wherein at least one of the massage bumps is fixed to the lifter and shaped in hemisphere.

9. A reclining massager system, comprising:

a) a base;

b) a back support to place a user's back and neck thereon when the user is seated in the base,

wherein the back support has a cover, first and second ends, wherein the first end is rotatably connected to the base in a controllably reclining format;

c) a rider making a lengthwise reciprocal movement between the first and second ends of the back support;

d) a pair of pulleys linked by a rope and respectively mounted in the first and second ends of the back support, wherein a predetermined portion of the rope is fixedly attached to the rider so that the pulley rotation enables the rider to generate the lengthwise reciprocal movement;

e) a lifter liftedly engaged to the rider so that the lifter makes a forward reciprocal movement perpendicular to the lengthwise reciprocal movement of the rider; and

f) massage bumps veiled by the cover and attached atop the lifter to massage along the user's back and neck in accordance with the relative movements of the rider and lifter.

10. The reclining massager system of claim 9 further comprising:

a) guide rails provided substantially parallel to the rope and between the first and second ends of the back support; and

b) guide rollers attached to the rider, wherein the guide rollers are rollably fit in the guide rails to facilitate the lengthwise reciprocation of the rider.

11. The reclining massager system of claim 9 wherein the lifter comprises:

a) a roller gear engaged to and powered by a first motor, wherein the first motor is fixed to the rider;

b) a bump support having a top portion and a bottom portion, wherein the massage bumps are mounted on the top portion; and

c) an engagement body downwardly extending from a bottom portion of the bump support, wherein a lower portion of the engagement body is releasably inserted in and fittingly supported by the rider, wherein an opening is formed through the engagement body to define inner walls, wherein one of the inner walls is configured to a rack gear so that the first roller gear is rollably engaged to the rack

gear, whereby the roller gear rotation by the first motor enables the lifter to make the forward reciprocal movement.

12. The reclining massager system of claim 9 wherein the lifter comprises:

a) a bump support having a top portion and a bottom portion, wherein the massage bumps are mounted on the top portion; and

b) a gear unit including a bolt gear downwardly extending from the bottom portion of the bump support, an elongated nut type gear having a circular outer periphery, a first gear incorporated on and along the circular outer periphery, and a second gear engaged to the first gear and connected to a first motor attached to the rider, wherein the bolt gear is releasably engaged in the nut type gear whose bottom end is rotatably attached to and supported by the rider, whereby the second gear rotation generates the first gear rotation and the subsequent rotation of the nut type gear enables the lifter to make the forward reciprocal movement in accordance with the

releasable engagement of the bolt gear and the nut type gear.

13. The reclining massager system of claim 9 wherein the massage bumps are partitioned to first and second pairs, wherein said each pair bumps are aligned parallel to the direction of the rider reciprocation.

14. The reclining massager system of claim 9 further comprising:

a) first and second bump holders propping and maintaining the first and second pair bumps, wherein the first and second bump holders are tapered toward each lower end thereof;

b) a first engagement member to rockingly engage the lower ends of the bump holders to the top portion of the lifter; and

c) a second engagement member to rollingly engage the massage bumps thereto.

15. The reclining massager system of claim 9 wherein the massage bumps each include a heater.

16. The reclining massager system of claim 9 wherein the heater is a heating lamp generating heat and infrared rays.

17. The reclining massager system of claim 9 wherein at least one of the massage bumps is fixed to the lifter and shaped in hemisphere.

18. A reclining massager system, comprising:

a) a base;

b) a back support to place a user's back and neck thereon when the user is seated in the base, wherein the back support has a cover, first and second ends, wherein the first end is rotatably connected to the base in a controllably reclining format;

c) a rider making a lengthwise reciprocal movement between the first and second ends of the back support, wherein the rider has at least one nut fixed thereto;

d) a threaded shaft geared through the nut and rotatably engaged at the first and second ends of the back support to generate the lengthwise reciprocal movement of the rider;

e) a lifter liftedly engaged to the rider so that the lifter makes a forward reciprocal movement perpendicular to the lengthwise reciprocal movement of the rider; and

f) massage bumps veiled by the cover and attached atop the lifter to massage along the user's back and neck in accordance with the relative movements of the rider and lifter.

19. The reclining massager system of claim 18 wherein the lifter comprises:

a) a roller gear engaged to and powered by a first motor, wherein the first motor is fixed to the rider;

b) a bump support having a top portion and a bottom portion, wherein the massage bumps are mounted on the top portion; and

c) an engagement body downwardly extending from a bottom portion of the bump support, wherein a lower portion of the engagement body is releasably inserted in and fittingly supported by the rider, wherein an opening is formed through the engagement body to define inner walls, wherein one of the inner walls is configured to a rack gear so that the first

roller gear is rollably engaged to the rack gear, whereby the roller gear rotation by the first motor enables the lifter to make the forward reciprocal movement.

20. The reclining massager system of claim 18 wherein the lifter comprises:

a) a bump support having a top portion and a bottom portion, wherein the massage bumps are mounted on the top portion; and

b) a gear unit including a bolt gear downwardly extending from the bottom portion of the bump support, an elongated nut type gear having a circular outer periphery, a first gear incorporated on and along the circular outer periphery, and a second gear engaged to the first gear and connected to a first motor attached to the rider, wherein the bolt gear is releasably engaged in the nut type gear whose bottom end is rotatably attached to and supported by the rider, whereby the second gear rotation generates the first gear rotation and the subsequent rotation of the nut type gear enables the lifter to make the forward reciprocal movement in accordance with the

releasable engagement of the bolt gear and the nut type gear.

21. The reclining massager system of claim 18 wherein the massage bumps are partitioned to first and second pairs, wherein said each pair bumps are aligned parallel to the direction of the rider reciprocation.

22. The reclining massager system of claim 18 further comprising:

a) first and second bump holders propping and maintaining the first and second pair bumps, wherein the first and second bump holders are tapered toward each lower end thereof;

b) a first engagement member to rockingly engage the lower ends of the bump holders to the top portion of the lifter; and

c) a second engagement member to rollingly engage the massage bumps thereto.

23. The reclining massager system of claim 18 wherein the massage bumps each include a heater.

24. The reclining massager system of claim 23 wherein the heater is a heating lamp generating heat and infrared rays.

25. The reclining massager system of claim 18 wherein at least one of the massage bumps is fixed to the lifter and shaped in hemisphere.